

ARES (OPZV) SERIES



Application

Telecom, UPS system, Utility system, Energy storage system, etc.



Technical Characteristics



Tubular gel technology battery.



Adopting PVC-SiO₂ separator.



Positive tubular plate.



Super long design life.



Adopting advanced gel phase SiO₂.



General Specification

Type	Nominal Voltage (V)	Rated Capacity (Ah)	Dimension (mm)				Weight (kg)
		C10	Length	Width	Height	Overall Height	
4OPzV200	2	200	103.0	206.0	356.0	389.0	18.0
6OPzV300	2	300	145.0	206.0	356.0	389.0	25.0
6OPzV400	2	400	145.0	206.0	473.0	505.0	31.5
7OPzV500	2	500	166.0	206.0	473.0	505.0	36.5
6OPzV600	2	600	145.0	206.0	646.0	678.0	45.0
8OPzV800	2	800	191.0	210.0	646.0	678.0	60.0
10OPzV1000	2	1000	233.0	210.0	646.0	678.0	72.5
12OPzV1200	2	1200	275.0	210.0	646.0	678.0	87.0
12OPzV1500	2	1500	275.0	210.0	795.0	827.0	105.5
16OPzV2000	2	2000	399.0	212.0	770.0	802.0	142.5
20OPzV2500	2	2500	487.0	212.0	770.0	802.0	176.5
24OPzV3000	2	3000	576.0	212.0	770.0	802.0	212.0