

313K SERIES



Application

Outdoor telecom, Power Systems, Other backup systems.



Technical Characteristics

Extra high cycling performance.

The shell is made of high temperature resistant material.

Super long design life.



General Specification

Type	Nominal Voltage (V)	Rated Capacity (Ah)		Dimension (mm)			Weight (kg)
		C10	Length	Width	Height	Overall Height	
HTB-200F	2	200	184.5	109.0	360.5	370.0	17.0
HTB-300F	2	300	185.0	130.0	360.5	370.0	22.0
HTB-400F	2	400	184.5	166.0	360.5	370.0	27.0
HTB-500F	2	500	184.5	194.5	360.5	370.0	32.5
HTB-600F	2	600	223.0	184.5	360.5	370.0	37.5
HTB-800F	2	800	188.0	315.5	361.5	317.0	53.5
HTB-1000F	2	1000	188.0	377.5	361.5	317.0	65.5
HTB-1200F	2	1200	264.0	232.0	502.0	514.0	88.0
HTB-1500F	2	1500	232.0	322.0	502.0	514.0	106.0
HTB-2000F	2	2000	232.0	456.0	502.0	514.0	150.0
12HTB100	12	100	390.0	108.0	232.0	287.0	35.0
12HTB150	12	150	546.0	125.0	310.0	310.0	55.5
12HTB170	12	170	546.0	125.0	310.0	310.0	60.5
12HTB100F	12	100	395.0	108.0	272.0	287.0	30.0
12HTB150F	12	150	550.0	125.0	270.0	283.0	47.0
12HTB170F	12	170	550.0	125.0	270.0	283.0	50.0
12HTB190F	12	190	559.0	125.0	303.0	316.0	57.5
12HTB200F	12	200	559.0	125.0	303.0	316.0	58.0
12HTB150FT	12	150	550.0	110.0	283.0	287.0	44.0